


AC Drive, Model: SET400G



- Universal AC Drive, covering more than 90% applications
- Powerful current vector control performance, low noise, excellent energy-saving effect
- Perfect software and hardware protection function
- Double line display
- Strong anti interfacing ability
- stable and reliable operation of the system
- Support user programmable control card

## Wiringdiagram of three-phase





- 1) Terminal represents the main circuit terminal and o represents the control circuit terminal.
- 2) 1.5kW~22kW built-in brake unit is standard configuration, without additional installation
- 3) The braking resistor is selected according to the user's needs, as detailed in the selection guide for braking resistors.

## **Electrical Specification**

Specification and model	Rated output current(A)	Adaptive motor power(kw)	Height(H) Width(W) Depth(D) (mm)	
SET400G-1R5G/2R2G	3.8/5.1	1.5/2.2	186*125*177	
SET400G-2R2G/4R0P	5.1/9	2.2/4		
SET400G-4R0G/5R5P	9/13	4/5.5		
SET400G-5R5G/7R5P	13/17 5.5/7.5 17/25 7.5/11		248*160*192	
SET400G-7R5P/11P				
SET400G-11G/15P				
SET400G-15G/18.5P	32/37	15/18.5	322*208*200	
SET400G-18.5G/22P	37/45	18.5/22		
SET400G-22G/30P	45/60	22/30		
SET400G-30G/37P	60/75 30/37		402*205*242	
SET400G-37G/45P	75/91	37/45	463*285*243	
ET400G-45G/55P 91/112 45/55				
SET400G-55G/75P	5G/75P 112/150 55/7		600*385*280	
SET400G-75G/90P	150/176	75/90		
SET400G-90G/110P	400G-90G/110P 176/210 90/100			
SET400G-110G/132P	210/253	100/132	700*473*322	
SET400G-132G/160P	253/304	132/160		
SET400G-160G/185P	304/340	160/185		
SET400G-185G/200P	340/377	185/200	930*579*395	
SET400G-200G/220P	377/426	200/220		
SET400G-220G/250P	ET400G-220G/250P 426/465 220/250			
SET400G-250G/280P	465/520	250/280	400010501005	
SET400G-280G/315P	520/585	280/315	1060*650*395	
SET400G-315G/355P	585/650	315/355		
SET400G-355G/400P	400G-355G/400P 650/725 355/400			
SET400G-400G/450P	725/820	400/450	1360*800*405	
SET400G-450G/500P	820/860	450/500		
SET400G-500G/550P	860/950	500/550	1175*840*415	

Note: SET400G series panel opening size: 147mm high and 79mm wide








Figure 2-3 Dimensions below 22kw plastic model

Figure 2-4 Boundary Dimensions of 30-500KW

## 2-4 Appearance and installation hole size

Power(kw)	A(mm)	B(mm)	H(mm)	W(mm)	D(mm)		Remark
	Installation dimension		Overalldimension			diameter (mm)	Nemark
1.5-4	113	172	186	125	177	5	
5.5-11	148	236	248	160	192	5	
15-22	190	305	322	208	200	6	
30-37	235	447	463	285	243	6.5	
45-75	260	580	600	385	280	7	
90-132	343	678	700	473	322	9	
160-200	449	903	930	579	395	12.5	
220-315	420	1030	1060	650	395	12.5	
355-450	520	1300	1360	800	405	12.5	
500	700	1130	1175	840	415	12.5	

GSTIN: 24AHPPP6852P1ZE, Website: www.sanketelectrotech.com